

ULTIMATE POWER SOLUTION (FZC)

The world's best dealer for Power Generation, Control System, & Power Solution

POWERED BY:



1250 KVA

3 PHASE

50 Hz

1375 KVA

60 Hz

3 PHASE

GENERATING SET MODEL (UPSC1250)

Output Ratings	Prime	Standby
380-415 V, 3ph, 50 Hz, 1500 rpm	1250 KVA	1375 KVA
	1000 KW	1100 KW
380-415 V, 3ph, 60 Hz, 1800 rpm	1375 KVA	1575 KVA
	1100 KW	1260 KW

ENGINE / TECHNICAL DATA

Ratings at 0.8 Power Factor

Engine Make	CUMMINS
Engine Model	KTA50-G3
Governing Type	Electrical
Number of Cylinder/ Arrangement	12/ V
Bore and Stroke (mm)	159 mm x 159 mm
Compression Ratio	13.9 : 1
Displacement (L)	50.3 L
Aspiration and Cooling	Turbocharged & After-cooled
Frequency regulation, steady state	±0.25%
Engine air flow	1746-1840 L/s
Exhaust temperature	475-525°C
Frequency and Engine Speed	50 Hz / 1500 rpm 60 Hz / 1800 rpm
Fuel Consumption @50% load	139 L/hr
@75% load	199 L/hr
@100% load	261 L/hr
@110% load	293 L/hr
Total oil capacity w/ filter	176.8 L
Engine capacity	160.9 L
Max Water Temperature	104°C
Thermostat	82-93°C

ALTERNATOR

Make	UPS / Leroy Somer
Model	UPS / LSA 50.2 L8
No. of bearings	1
Pole	4
Coupling	Direct
Exciter Type	AREP
Insulation	H/H
Degree of protection	IP23
AVR Model	D350
Altitude	≤1000m
Winding Pitch	2/3
Winding Leads	6/12

CONTROL PANEL

Make	DeepSea
Model	6110/20 SERIES

The DSE 6110/20 Seeries., is an Auto Start Control for single genset application. It includes a LCD display which clearly shows the status of engine all the times. This module can either programmed using the front panel or by using configuraton sale PC software.

Metering and Alarm Indications:

- Generator frequency
- UnderSpeed, Overspeed
- Generator volts (L-L, L-N)
- Generator current
- Engine oil pressure
- Engine coolant temperature
- Hours run counter
- Battery volts
- Fail to start/stop
- Emergency stop
- Failed to reach loading voltage/frequency
- Charge fail
- LOW DC voltage
- CAN diagnostic and CAN fail/error



CERTIFIED BY:



Tel: +971 6 5570722
Fax: +971 6 5570733

P.O. Box: 122333

F3-18, Sharjah Airport Free Zone (SAIF Zone)

E-mail: info@upsgenerator.com
Web: www.upsgenerator.com

STANDARD SPECIFICATIONS

1250 KVA

3 PHASE

50 Hz

1375 KVA

3 PHASE

60 Hz

1. ENGINE

Cummins four stroke heavy duty high performance industrial type diesel engine.

2. ENGINE FILTERATION SYSTEM

- Cartridge type dry air filter.
- Cartridge type fuel filters.
- Full flow lube oil filter.

All filters have replaceable elements.

3. COOLING RADIATOR

Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for de-ration factors)

4. EXHAUST SYSTEM

Exhaust gas flow 4011-4295 L/s
Maximum allowable back pressure 7 (kPa)

5. CIRCUIT BREAKER TYPE

3 pole MCCB. (4 pole is optional)

6. Fuel System

The baseframe design is not incorporated with an integral fuel tank.

7. ALTERNATOR

7.1 INSULATION SYSTEM

- The insulation system is Class H.
- All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at $\pm 1\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.

8. MOUNTING ARRANGEMENT

8.1 COUPLING

- The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

8.2 ANTI-VIBRATION MOUNTING PADS

- Anti-Vibration pads are affixed between the Engine/ Alternator feet and the Basframe thus ensuring complete vibration isolation of the rotating assembly.

8.3 SAFETY GUARDS

- The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

9. FACTORY TEST

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and its systems are checked before dispatch.

10. EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

11. DOCUMENTATION

Operation & Maintenance manual, Circuit wiring diagrams and Commissioning/Fault Finding instruction leaflets are accompanied with the Generator.

12. QUALITY STANDARDS

The equipment meets the following standards: B84999, B65000, BS5514 IEC 60034, VDE0530, NEMA MG 1.22 and ISO8528.


13. WARRANTY

All of the Generating Sets are covered under a warranty policy for a period of 12 months or 1000 working hours, Warranty of the equipment is in line with manufacturers warranty terms & conditions.
(check warranty statement for more details, as it may vary for different countries)

In line with continuous product development, we reserve the right to change specifications without notice.

STANDARD GENERATOR DIMENSION

Standard Generator




Length, L: 4980 mm

Height, H: 2399 mm

Width, W: 2069 mm

Generator with Soundproof and Containerize Canopy



Length, L: 12192 mm

Height, H: 2896 mm

Width, W: 2438 mm