



ULTIMATE POWER SOLUTION (FZC)

Prime

POWERED BY:



706 KVA

3 PHASE

50 Hz

802 KVA

3 PHASE

60 Hz

GENERATING SET MODEL (UPSP706)

Output Ratings

	Prime	Standby
380-415 V, 3ph, 50 Hz, 1500 rpm	706 KVA	780 KVA
	559 KW	624 KW
380-415 V, 3ph, 60 Hz, 1800 rpm	802 KVA	888 KVA
	642 KW	710 KW

ENGINE / TECHNICAL DATA

Ratings at 0.8 Power Factor

Engine Make	PERKINS	
Engine Model	2806A-E18TTAG4	
Governing Type	Electronic	
Number of Cylinder/ Arrangement	6/ Vertical In-line	
Bore and Stroke (mm)	145 x 183 mm	
Compression Ratio	14:1	
Displacement (L)	18.1 L	
Aspiration/ Cooling	Parallel turbocharged and air-to-air chargecooled	
Combustion System	Direct Injection	
Rotation from Flywheel End	Anti-clockwise, viewed on flywheel	
Total Lubrication System Capacity	68 L	
Total Coolant Capacity	110 L	
Cycle	4 Stroke	
Frequency and Engine Speed	50 Hz / 1500 rpm	60 Hz / 1800 Rpm
Fuel Consumption	@50% load	196 G/Kwh
	@75% load	191 G/Kwh
	@100% load	195 G/Kwh
	@110% load	195 G/Kwh
Exhaust temperature	461°C	433°C

ALTERNATOR

Make UPS / LEROYSOMER (TAL)

Model

No. of bearings 1

Insulation H

Coupling Direct

Exciter Type SHUNT

Wires 6/12

Degree of protection IP23

Winding Pitch 2/3

Overspeed 2250 mn⁻¹

Voltage Regulation ±1%

CONTROL PANEL

Make DeepSea

Model 6110/20 SERIES

The DSE 6110/20 Series, is an Auto Start Control for single genset application. It includes a LCD display which clearly shows the status of engine all the times. This module can either programmed using the front panel or by using configurator sale PC software.

Metering and Alarm Indications:

- Generator frequency
- UnderSpeed, Overspeed
- Generator volts (L-L, L-N)
- Generator current
- Engine oil pressure
- Engine coolant temperature
- Hours run counter
- Battery volts
- Fail to start/stop
- Emergency stop
- Failed to reach loading voltage/frequency
- Charge fail
- LOW DC voltage
- CAN diagnostic and CAN fail/error



CERTIFIED BY:



STANDARD SPECIFICATIONS

706 KVA**3 PHASE****50 Hz****802 KVA****3 PHASE****60 Hz**

1.ENGINE

Perkins four stroke heavy duty high performance industrial type diesel engine.

2.ENGINE FILTERATION SYSTEM

- Cartridge type dry air filter.
- Cartridge type fuel filters.
- Full flow lube oil filter.

All filters have replaceable elements.

3.COOLING RADIATOR

Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for de-rating factors)

4.EXHAUST SYSTEM

Exhaust gas flow	119 m ³ /min
Maximum allowable back pressure	10 (kPa)

5.CIRCUIT BREAKER TYPE

3 pole MCCB. (4 pole is optional)

6.Fuel System

The baseframe design is not incorporated with an integral fuel tank.

7. ALTERNATOR

7.1 INSULATION SYSTEM

- The insulation system is Class H.
- All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at $\pm 1\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.

8.MOUNTING ARRANGEMENT

8.1 COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

8.2 ANTI-VIBRATION MOUNTING PADS

- Anti-Vibration pads are affixed between the Engine/ Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

8.3 SAFETY GUARDS

- The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

9.FACTORY TEST

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and its systems are checked before dispatch.

10.EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

11. DOCUMENTATION

Operation & Maintenance manual, Circuit wiring diagrams and Commissioning/Fault Finding instruction leaflets are accompanied with the Generator.

12.QUALITY STANDARDS

The equipment meets the following standards: B84999, B65000, BS5514 IEC 60034, VDE0530, NEMA MG 1.22 and ISO8528.


13. WARRANTY

All of the Generating Sets are covered under a warranty policy for a period of 12 months or 1000 working hours, Warranty of the equipment is in line with manufacturers warranty terms & conditions. (check warranty statement for more details, as it may vary for different countries)

In line with continuous product development, we reserve the right to change specifications without notice.

STANDARD GENERATOR DIMENSION

Standard Generator




Length, L: 4200 mm

Height, H: 2250 mm

Width, W: 1720 mm

Weight: 6000 KG

Generator with Soundproof Canopy



Length, L: 5800 mm

Height, H: 2400 mm

Width, W: 2240 mm

Weight: 6500 KG